

FLEXTILE GROUT REFINISHER & APPLICATOR

BASIC USE

Flextile Grout refinisher is a water based grout sealer, which does not contain any VOC.

Designed as a finish top coat for Portland cement based sanded and unsanded grouts, Flextile Grout Refinisher dries to a matt finish which maintains the normal texture of the grout joint. It is ideal for re-coloring faded or unevenly colored grout joints, and also acts as a grout sealer to improve cleanability.

LIMITATIONS

Flextile Grout refinisher should not be used in pools, hot tubs or other areas subjected to continuous underwater exposure.

FEATURES

- No VOC content
- Improve stain resistance and cleanability.
- Ideal for re-colouring faded or unevenly coloured grout joints.

COVERAGE

Approximately 5-28 m² (50 to 300 sq. ft.) depending on the joint width and tile size.

INSTALLATION

SURFACE PREPARATION

Grouts must be thoroughly cured and dry, and free from all efflorescence, sealers, wax or other surface contamination. Saturate grout joints with water and clean with a solution of 1 part muriatic or sulfamic acid in 9 parts water to remove any efflorescence or lime deposits, then scrub joints with a nylon scouring pad and clean water. Thoroughly rinse with clean water and allow to dry.

APPLICATION

- Remove any excess dirt and grease from the grout surface. Use rubber gloves.
- Shake the bottle of grout refinisher, unscrew wheel applicator top and remove the red inner seal from the neck of the bottle. Replace applicator top.
- Holding the bottle in a near vertical position, squeeze gently and continuously roll the grout refinisher along the grout line until material appears. Continue coating grout joint in **ONE DIRECTION ONLY**, either vertically or horizontally, rolling away from you and squeezing the bottle only as needed. Be sure to do only the grout joints in one direction, then do the cross joints. Coat a small area at a time.
- For hard to reach place such as around fixtures and in corners, use a brush in place of the roller applicator. A brush may also be used to coat wider grout joints.
- Allow 24 hours to cure, prior to allowing traffic. Avoid washing surface for 48 hours.

SAFETY

Refer to Flextile Material Safety Data Sheet for detailed health and safety information.

AVAILABILITY AND COSTS

Flextile Grout Refinisher is available from Flextile Ltd. and its distributors in 236ml (8fl.oz) bottle. Available in colors to match Flextile Polymer Modified Sanded and Unsanded Grout colors.

Cost: Data supplied upon request.

WARRANTY

Flextile warrants that this product is of merchantable quality and is suitable for the purpose for which it is intended. Flextile's liability under this warranty shall be limited to replacement of its product found to be defective or, at its option, a refund of the purchase price.

TECHNICAL SERVICES

Flextile maintains a well equipped laboratory able to test its products in conjunction with the products with which they are used. Technical assistance for use of Flextile products is available upon request

March 7, 2015

For job specific installation systems, recommendations, project warranty information, or for assistance with installation specifications, please contact Flextile's technical department.

Toronto, ON – Email: mzerey@flextile.net

Toll Free 1-800-699-3623

Tel 1-416-255-1111

Fax 1-416-255-1729

Montreal, QC – Email: mzerey@flextile.net

Toll Free 1-800-699-3623

Tel 1-514-345-8666

Fax 1-514-345-8825

Burnaby, BC – Email: mboldt@flextile.net

Toll Free 1-888-236-4486

Tel 1-604-420-4914

Fax 1-604-420-0936

www.flextile.net