

**FLEXITILE LTD**  
**Material Safety Data Sheet**  
**FS FAST SET SCREED CONCENTRATE**

MANUFACTURER:  
ONTARIO  
 121-30th Street,  
 Etobicoke, ON.  
 M8W 3C1  
 Tel: (416) 255-1111  
 FAX: (416) 255-1729  
 IN CASE OF EMERGENCY.

FLEXITILE LTD.  
QUEBEC  
 555, Rue Locke  
 Ville St. Laurent, QC  
 H4T 1X7  
 Tel: (514) 345-6666  
 FAX: (514) 345-8825  
 CALL CANUTEC (613) 996-6666

BRITISH COLUMBIA  
 2829 Lake City Way  
 Burnaby, BC  
 V5A 2Z6  
 Tel: (644) 420-4914  
 FAX: (604) 420-0936

**Material Identification**

PRODUCT IDENTIFIER..... FS FAST SET SCREED CONCENTRATE  
 WHMIS CLASSIFICATION..... D.2 E

**Hazardous Ingredients of Materials**

| CHEMICAL IDENTITY        | CONC.  | CAS#/NA#/UN# | ACGIH TLV           | OSHA PEL             |
|--------------------------|--------|--------------|---------------------|----------------------|
| PORTLAND CEMENT          | 10-25% | 65997-15-1   | 10mg/m <sup>3</sup> | 15mg/ m <sup>3</sup> |
| CALCIUM ALUMINATE CEMENT | 30-70% | 65997-16-2   | 10mg/m <sup>3</sup> | 15mg/ m <sup>3</sup> |
| GYPNUM                   | 10-30% | 13397-24-5   | 15mg/m <sup>3</sup> | 10 mg/m <sup>3</sup> |
| CALCIUM CARBONATE        | 5-15%  | 1317-65-3    | 10mg/m <sup>3</sup> | 5mg/ m <sup>3</sup>  |

This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive toxicity.  
 All ingredients are listed within the US TSCA and Canadian DSL.

**Physical Data For Product**

|                           |                                  |                             |             |
|---------------------------|----------------------------------|-----------------------------|-------------|
| PHYSICAL STATE.....       | POWDER                           |                             |             |
| ODOUR AND APPEARANCE..... | DARK GREY DRY MIX, CEMENT ODOUR. |                             |             |
| ODOUR THRESHOLD.....      | N/D                              | SPECIFIC GRAVITY.....       | 1.2 - 1.6   |
| VAPOUR PRESSURE.....      | N/D                              | VAPOUR DENSITY (air=1)..... | N/D         |
| EVAPORATION RATE.....     | N/D                              | BOILING POINT.....          | N/D         |
| FREEZING POINT.....       | N/D                              | pH.....                     | 11 when wet |
| DENSITY (g/ml).....       | N/D                              | SOLUBILITY IN WATER         | INSOLUBLE   |
| CALCULATED VOC CONTENT    | 0 gm/L                           |                             |             |

**Fire and Explosion Hazard of Product**

|                                  |  |
|----------------------------------|--|
| CONDITIONS OF FLAMMABILITY.....  | STABLE   |
| MEANS OF EXTINCTION.....         | NOT APPLICABLE   |
| FLASH POINT.....                 | NOT FLAMMABLE OR COMBUSTIBLE   |
| UPPER EXPLOSION LIMIT (%)..      | NOT ESTABLISHED  |
| LOWER EXPLOSION LIMIT (%)..      | NOT ESTABLISHED  |
| FIRE EXTINGUISHING MATERIALS     | WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL OR FOAM                        |
| SPECIAL FIRE FIGHTING PROCEDURES | WEAR STANDARD FIRE FIGHTING GEAR WITH SELF-CONTAINED BREATHING APPARATUS |

**Reactivity Data**

|                                    |  |
|------------------------------------|--|
| CHEMICAL STABILITY.....            | STABLE   |
| INCOMPATIBLE MATERIALS.....        | STRONG OXIDISING AGENTS, STRONG ACIDS & STRONG BASES.  |
| CONDITIONS TO AVOID.....           | KEEP DRY UNTIL USED  |
| HAZARDOUS DECOMPOSITION PRODUCTS.. | CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN, AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS. |
| HAZARDOUS POLYMERIZATION           | WILL NOT OCCUR   |

---

### Toxicological Properties of Product

---

THE HAZARDOUS INGREDIENTS WHEN IN CONTACT WITH WATER PRODUCE AN ALKALINITY LEVEL OF pH 10 TO pH 11. THIS LEVEL OF ALKALINITY CAN CAUSE SKIN AND EYE IRRITATION.

ROUTES OF ENTRY:SKIN CONTACT, EYE CONTACT, INHALATION, INGESTION.

EFFECTS OF ACUTE EXPOSURE :

CEMENT AND WET CEMENT MIXTURES CAN DRY SKIN, CAUSE ALKALI BURNS, IRRITATE THE EYES AND THE UPPER RESPIRATORY TRACT. INGESTION CAN CAUSE IRRITATION OF THE THROAT.

EFFECTS OF CHRONIC EXPOSURE:

CEMENT DUST CAN CAUSE INFLAMMATION OF THE TISSUE LINING, THE INTERIOR OF THE NOSE, AND THE CORNEA (WHITE) OF THE EYE. HYPER SENSITIVE PEOPLE MAY DEVELOPED ALLERGIC DERMATITIS. REPEATED INHALATION OF DUST MAY RESULT IN SILICOSIS.

CARCINOGENICITY NTP – YES IARC – YES OSHA – YES

CRYSTALLINE SILICA – IARC GROUP 1 AGENT

---

### Preventive Measures

---

PERSONAL PROTECTIVE EQUIPMENT.....

USE APPROVED (OHSA) DUST RESPIRATOR RATED N95 WHEN MIXING. USE A LOCAL VENTILATION. WEAR IMPERVIOUS RUBBER GLOVES. WEAR A FACE SHIELD OR SAFETY GLASSES WITH SHIELDS.

VENTILATION.....

VENTILATION SHOULD BE SUFFICIENT IN VOLUME AND DISTRIBUTION TO MAINTAIN DUST EXPOSURE BELOW THE TWAEV.

LEAK AND SPILL PROCEDURES.....

PICK UP SOLIDS. AVOID DUSTS ACCUMULATION. MOP UP OR ABSORB WITH AN INERT MATERIAL. SCRAPE UP AND DISPOSE INTO A DISPOSAL CONTAINER.

WASTE DISPOSAL.....

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT.

WEAR AN EYE PROTECTION APPARATUS. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID BREATHING OF VAPOURS.

STORAGE REQUIREMENTS..... STORE IN A DRY AREA.

SPECIAL SHIPPING INFORMATION..... NOT REGULATED

---

### First Aid Measures

---

SPECIFIC FIRST AID PROCEDURES.....

FLUSH EYES AND CONTAMINATED SKIN WITH ABUNDANT WATER. SEEK MEDICAL ATTENTION. IF INGESTED, DRINK PLENTY OF WATER AND CONSULT A PHYSICIAN. IN CASE OF DISCOMFORT BY VAPOURS OR DUSTS, MOVE TO A VENTILATED AREA. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

---

### Preparation Date of Material Safety Data Sheet

---

PREPARED BY.....

CHIEF CHEMIST

PHONE NUMBER OF PREPARER.....

(416) 255-1111 FAX: (416) 255-1729

DATE PREPARED.....

26 Oct., 2016

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

...FLEXTILE LTD.

N/D = NOT DETERMINED