

FLEXTILE LTD
Material Safety Data Sheet
WP-980 WATERPROOF & CRACK ISOLATION MEMBRANE

MANUFACTURER:
ONTARIO
 121-30th Street,
 Etobicoke, ON.
 M8W 3C1
 Tel: (416) 255-1111
 FAX: (416) 255-1729
 IN CASE OF EMERGENCY.

FLEXTILE LTD.
QUEBEC
 555, Rue Locke
 Ville St. Laurent, QC
 H4T 1X7
 Tel: (514) 345-6666
 FAX: (514) 345-8825
 CALL CANUTEC (613) 996-6666

BRITISH COLUMBIA
 2829 Lake City Way
 Burnaby, BC
 V5A 2Z6
 Tel: (644) 420-4914
 FAX: (604) 420-0936

Material Identification and Use

PRODUCT IDENTIFIER	WP-980 WATERPROOF & CRACK ISOLATION MEMBRANE
PRODUCT USE	WATER-PROOFING FOR FLOORING INSTALLATION.
WHMIS CLASSIFICATION	NOT CONTROLLED

Hazardous Ingredients of Materials

CHEMICAL IDENTITY	CONC.	CAS#/NA#/UN#	LD(50)	LC(50)
THIS PRODUCT CONTAINS NO HAZARD INGREDIENTS AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 OR SECTION 13 OF THE CANADIAN HAZARDOUS PRODUCT ACT. ALL INGREDIENTS ARE LISTED WITHIN OR EXEMPTED FROM US TSCA AND CANADIAN DSL.				

Physical Data for Product

PHYSICAL STATE.....	SLIGHTLY VISCOUS LIQUID
ODOUR AND APPEARANCE.....	MILD ODOUR, DARK BLUE LIQUID.
SPECIFIC GRAVITY.....	1.14
VAPOUR PRESSURE.....	NOT AVAILABLE
VAPOUR DENSITY (air=1).....	HEAVIER THAN AIR.
EVAPORATION RATE.....	SLOWER THAN N-BUTYL ACETATE.
BOILING POINT.....	100C
FREEZING POINT.....	N/D
CALCULATED VOC.....	< 10 gm/litre

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY.....	STABLE
MEANS OF EXTINCTION.....	WATER, CO2, OR DRY CHEMICAL.
FLASHPOINT AND METHOD OF DETERMINATION.....	N/D
UPPER EXPLOSION LIMIT (% BY VOL)..	N/D
LOWER EXPLOSION LIMIT (% BY VOL)..	N/D
AUTO-IGNITION TEMPERATURE.....	N/D
FLAMMABILITY CLASSIFICATION.....	NON-FLAMMABLE LIQUID
HAZARDOUS COMBUSTION PRODUCTS.....	N/D
EXPLOSION DATA.....	NON-EXPLOSIVE
SENSITIVITY TO STATIC DISCHARGE...	N/D
SPECIAL FIREFIGHTING PROCEDURES.....	FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

Reactivity Data

CHEMICAL STABILITY.....	STABLE
INCOMPATIBLE MATERIALS.....	NONE KNOWN.
CONDITIONS TO AVOID.....	KEEP FROM FREEZING.
HAZARDOUS DECOMPOSITION PRODUCTS..	UNDER SEVERE THERMAL DEGRADATION, LOW MOLECULAR-WEIGHT COMPOUNDS WILL BE FORMED.

Toxicological Properties of Product

ROUTES OF ENTRY

SKIN CONTACT.....	MAY CAUSED IRRITATION ON PROLONGED CONTACT.
SKIN ABSORPTION.....	N/D.
EYE.....	MAY CAUSE IRRITATION.
INHALATION.....	MAY CAUSE HEADACHE AND NAUSEA.
INGESTION.....	MAY CAUSE DISCOMFORT.
ACUTE OVER EXPOSURE EFFECTS.....	... AS ABOVE
CHRONIC OVER EXPOSURE EFFECTS....	N/D
EXPOSURE LIMITS.....	N/D
IRRITANCY OF PRODUCT.....	N/D
SENSITIZATION TO MATERIAL.....	N/D
CARCINOGENICITY, REPRODUCTIVE EFFECTS.....	N/D
TERATOGENICITY, MUTAGENICITY.....	N/D
TOXICOLOGICALLY SYNERGISTIC PRODUCTS.....	N/D

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT.....	RESPIRATORY PROTECTION IS NOT GENERALLY REQUIRED DURING NORMAL USE AND HANDLING. CHEMICAL RESISTANT NITRILE, NEOPRENE OR RUBBER GLOVES, PROTECTIVE CLOTHING, FACE SHIELD OR CHEMICAL GOGGLES TO PREVENT SKIN AND EYE CONTACT.
VENTILATION.....	USE LOCAL (EXHAUST) VENTILATION.
LEAK AND SPILL PROCEDURES.....	ABSORB WITH PAPER, SAND OR SAWDUST. PLACE IN A CONTAINER.
WASTE DISPOSAL.....	DISCARD OR DISPOSE OF WASTE IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL & FEDERAL REGULATIONS.
HANDLING PROCEDURES AND EQUIPMENT.	AVOID EYE AND SKIN CONTACT.
STORAGE REQUIREMENTS.....	PROTECT FROM FREEZING.
SPECIAL SHIPPING INFORMATION.....	NOT REGULATED

First Aid Measures

SPECIFIC FIRST AID PROCEDURES.....	FLUSH EYES WITH ABUNDANT WATER. WASH SKIN WITH SOAP AND WATER. IN CASE OF INGESTION, SEEK MEDICAL ATTENTION.
------------------------------------	--

Preparation Date of Material Safety Data Sheet

PREPARED BY.....	CHIEF CHEMIST
PHONE NUMBER OF PREPARER.....	416-255-1111 FAX: 416-255-1729
DATE PREPARED.....	26 Oct., 2016

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

..FLEXITILE LTD.

N/D = NOT DETERMINED