

## Safety Data Sheet

66

### SECTION 1: IDENTIFICATION

Product: 66 Flexlite Lightweight Mortar  
Product Use: Polymer-modified lightweight mortar  
Manufacturer Information:

#### Ontario

121 - 30<sup>th</sup> Street  
Etobicoke, On.  
M8W 3C1  
Tel: (416) 255-1111  
Fax: (416) 255-1729

#### British Columbia

2829 Lake City Way  
Burnaby, BC  
V5A 2Z6  
Tel: (644) 420-4914  
Fax: (604) 420-0936

IN CASE OF EMERGENCY CALL CANUTEC (613) 996-6666

### SECTION 2: HAZARDS IDENTIFICATION

Classification of the chemical

#### WHMIS Classification

Class D2A, D2B, E



#### GHS Signal Word

#### GHS Classification:

Skin corrosion / irritation  
Serious eye damage / eye irritation  
Skin Sensitization  
Carcinogenicity  
Specific Target Organ Systemic Toxicity (STOT) SE  
Specific Target Organ Systemic Toxicity (STOT) RE

#### GHS Hazard Statements

#### GHS Hazard Statements

H315  
H317  
H318  
H335  
H350

#### Danger

Category 1 Causes skin irritation  
Category 1 Causes serious eye damage  
Category 1 May cause an allergic skin reaction  
SECategory 1A May cause cancer if inhaled  
Category 3 May cause respiratory irritation  
Category 1 Causes damage to organs through prolonged exposure if inhaled  
Causes skin irritation, may cause an allergic skin reaction, causes serious eye damage; may cause respiratory irritation; may cause cancer; causes damage to organs through prolonged or repeated exposure.

Causes skin irritation  
May cause an allergic skin reaction  
Causes serious eye damage  
May cause respiratory irritation.  
May cause cancer if inhaled.

## Safety Data Sheet

**66**

---

H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
GHS Precautions	Description
Code	Obtain special instructions before use.
P201	Do not handle until all safety precautions have been read and understood.
P202	Do not breathe dust.
P260	Wash skin thoroughly after handling.
P264	Do not eat, drink or smoke when using this product.
P270	Use only outdoors or in a well-ventilated area.
P271	Contaminated work clothing should not be allowed out of the workplace.
P272	Wear protective gloves and eye protection.
P280	If on skin: Wash with plenty of water.
P302+P352.A	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P304+P340	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P305+P351+P338	If exposed or concerned: Get medical advice/attention. Immediately call a POISON CENTER.
P308+P313	Call a POISON CENTER if you feel unwell.
P310	Get medical advice/attention if you feel unwell.
P312	Specific treatment (see supplementary instructions on this label)
P314	If skin irritation or rash occurs: Get medical advice/attention.
P321.A	Take off contaminated clothing and wash it before reuse.
P333+P313	Store in a well-ventilated place. Keep container tightly closed.
P362+P364	Store locked up.
P403+P233	Dispose of contents/container in accordance with applicable regulations.
P405	
P501	

---

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Name	% by Weight	CAS No.	Classification
Silica Sand, Crystalline quartz	40 - 70	14808-60-7	Carc. 1A, H350 STOT RE 1, H372
Portland Cement	30 - 45	65997-15-1	Eye damage 1, H318 Skin irritant 2, H315 Skin sensitizer 1, H317
Calcium Formate	0.2 - 5.0	544-17-2	STOT SE 3, H335 Eye damage 1, H318

## Safety Data Sheet

66

---

### SECTION 4: FIRST AID MEASURES

---

**General** In case of accident or illness, seek medical attention immediately.

**Eye Contact** Flush eyes and contaminated skin with abundant water. Seek medical attention immediately.

**Skin Contact** Remove contaminated clothing immediately. Wash skin immediately with soap and abundant water.

**Inhalation** If breathing is irregular or stopped, administer artificial respiration. Move to a well ventilated area. Seek medical attention immediately.

**If Ingested** Severely irritating. Do not induce vomiting. Drink lots of water or milk to dilute. Do not give anything by mouth to an unconscious person. Seek medical attention immediately.

### SECTION 5: FIRE FIGHTING MEASURES

---

<b>Extinguishing Media</b>	Water spray, carbon dioxide, dry chemical or foam
<b>Unsuitable Extinguishing Media</b>	None in particular
<b>Hazardous Combustion Products</b>	Do not inhale explosion and combustion gases
<b>Explosive Properties</b>	N/A
<b>Oxidizing Properties</b>	N/A
<b>Special Firefighting Procedures</b>	Wear standard fire fighting gear with self-contained breathing apparatus.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**Special Protection** Exposure to spilled material may be irritating or harmful. Wear personal protective equipment.

**Protective Equipment** Refer to Section 8 on this Safety Data Sheet for appropriate personal protection equipment.

Pick up solids and avoid dust accumulation. Use an appropriate scoop to remove large amounts of material while smaller quantities may be swept up. Avoid the use of water as material becomes alkaline when wet.

**Waste Disposal** Dispose of in accordance with local, state and federal regulations.

**Environmental Precautions** Do not allow product to enter drains or waterways. Do not allow material to contaminate ground water system. Refer to Section 13 for disposal information.

### SECTION 7: HANDLING AND STORAGE

---

Wear personal protective equipment. Avoid contact with skin and eyes, inhalation of vapours and mists.

Contaminated clothing should be changed before entering eating areas. Do not eat or drink in work areas.

Do not use any empty containers before they are cleaned.

**Protective Equipment** Refer to Section 8 on this Safety Data Sheet for appropriate personal protection equipment.

Wash thoroughly after handling.

**Storage** Store in a cool, adequately ventilated, dry area. Keep containers tightly closed when not in use

## Safety Data Sheet

66

### SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### EXPOSURE LIMITS

Chemical Name	CAS No.	ACGIH TLV	OSHA PEL
Silica Sand, Crystalline Quartz	14808-60-7	0.025 mg/m <sup>3</sup> TWA (respirable fraction)	0.1 mg/m <sup>3</sup> TWA (respirable)
Portland Cement	65997-15-1	1 mg/m <sup>3</sup> TWA (respirable, containing no asbestos and <1% crystalline silica)	15 mg/m <sup>3</sup> TWA (total dust), 5 mg/m <sup>3</sup> TWA (respirable)

#### ENGINEERING CONTROL METHODS:

**Ventilation** Use local exhaust ventilation or other engineering controls to minimize exposures.

**Eye Protection:** Wear safety glasses with side shields or face shield when handling this product. Have an eye wash station available.

**Skin protection** Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt.

**Hand Protection** Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

**Respiratory Protection** Use approved (OSHA) dust respirator rated n95 when mixing .

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Solid
Odour and appearance	Odourless White powder
Odour threshold	N/A
Specific gravity	1.2 – 1.6
Boiling point	N/A
Freezing point	N/A
pH	11 when wet
Flash point	N/A
Upper/Lower flammability or explosive limits	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A
Explosive properties	N/A
Oxidizing properties	N/A
Solubility in water	Dispersable
Solubility in oil	N/D
Octanol/Water coefficient	N/D
Calculated VOC content	0 g/l

### SECTION 10: STABILITY AND REACTIVITY

## Safety Data Sheet

**66**

---

Chemical stability	Stable
Incompatible materials	Strong oxidizing agents, strong acids, strong bases
Conditions to avoid	Keep dry until used
Hazardous decomposition products	CO, CO <sub>2</sub> , NO <sub>x</sub> , and other unidentified organic compounds

### SECTION 11: TOXICOLOGICAL INFORMATION

---

#### Toxicological information based on the individual components.

<b>Chemical Name</b>	<b>CAS No.</b>	<b>LD50/LC50</b>
Silica Sand, Crystalline Quartz	14808-60-7	ORAL LD50 (rat) 500 mg/kg
Portland Cement	65997-15-1	N/Av
Calcium Formate	544-17-2	Oral LD50 2650 mg/kg (rat)

**Routes of entry** skin contact, eye contact, ingestion, inhalation

**Effects of acute exposure** irritate the eyes and upper respiratory tract. Ingestion can cause throat irritation.

**Effects of chronic exposure** cement dust can cause inflammation of tissue lining the nasal interior and the eye cornea. Hypersensitive persons may develop allergic dermatitis.

Skin corrosion	In both dry and wet forms can dry skin and cause alkali burns
Serious eye damage / irritation	Can cause moderate irritation, tearing, and reddening
Respiratory or skin sensitization	May cause an allergic skin reaction, and respiratory irritation
Germ cell mutagenicity	No data available.
Carcinogenicity	This product contains crystalline silica. Crystalline silica (respirable size) is classified as carcinogenic by inhalation by: IARC (Group 1), ACGIH (Group A2), NTP (Group 1), OSHA (Select carcinogen). Cement is not listed as a carcinogen by IARC or NTP; however, cement contains trace amounts of crystalline silica and hexavalent chromium which are classified by IARC and NTP as known human carcinogens.
Reproductive toxicity	No data available
STOT-single exposure	May cause respiratory irritation
STOT-repeated exposure	May cause lung damage upon repeated or prolonged exposure
Aspiration hazard	repeated inhalation of dust may result in silicosis

### SECTION 12: ECOLOGICAL INFORMATION

---

Ecotoxicity	N/A
Persistence and degradability	N/A
Bioaccumulative potential	N/A
Mobility in soil	N/A
Other adverse effects	N/A

Revision Date: 03/05/2020

## Safety Data Sheet

66

---

List of components with eco-toxological properties

Silica sand

LC50 Aquatic acute toxicity carp >10,000 mg/l 72 h

Calcium formate

Acute toxicity (fish) 96 h Lc50 Brachydanio rerio  $\geq$  1000 mg/l (static)

### SECTION 13: DISPOSAL CONSIDERATIONS

---

**Handling for disposal** Handle waste as per recommendations in Section 7.

Dispose of in an approved landfill. Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

### SECTION 14: TRANSPORT INFORMATION

---

Consult Bill of Lading for transportation information.

Canadian TDG : not regulated

US DOT: not regulated

IATA: not regulated

### SECTION 15: REGULATORY INFORMATION

---

#### Canadian Information:

Canadian WHMIS Classification: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Controlled Products Regulations (CPR). Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL). It contains components listed on the Canadian HPA Ingredient Disclosure List. It contains Crystalline silica, quartz.

#### US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above the minimum concentrations.

#### U.S. State Right To Know Laws

California Proposition 65: Warning! This product contains a chemical known to the State of California to cause cancer. It contains Crystalline silica, quartz.

Other State Right to Know Law:

MA Portland Cement, Crystalline Silica, Quartz

NJ Portland Cement, Crystalline Silica, Quartz

PA Portland Cement, Crystalline Silica, Quartz

RI Portland Cement, Crystalline Silica, Quartz

MN Portland Cement, Crystalline Silica, Quartz

---

### SECTION 16: OTHER INFORMATION

Revision Date: 03/05/2020

Page 6 of 7

## Safety Data Sheet

66

---

This Safety Data Sheet is prepared to comply with the Canadian Workplace Hazardous Materials Information System (WHMIS) and the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

**HMIS rating: Health -- 2 Flammability -- 1 Reactivity -- 0**

See **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION** for personal protective equipment recommendations.

---

### PREPARATION DATE OF SAFETY DATA SHEET

---

**Prepared by** Technical department

**Phone number of preparer** (416) 255-1111 FAX: (416) 255-1729

**Date prepared** 7th August, 2015

Flextile Ltd. assumes no responsibility for injury to consumer or third persons caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd. assumes no responsibility for injury to consumer or third persons caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, consumer assumes the risk in use of the material.

The information and recommends set forth herein are believed to be accurate as some of the information is derived from information provided to Flextile Ltd. from suppliers and because Flextile Ltd. has no control over the conditions of handling and use. Flextile Ltd. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Flextile Ltd. assumes no responsibility for use or reliance thereon. It is the responsibility of the user to comply with all applicable federal, provincial, state, and local laws and regulations.