

FLEXITILE LTD
Material Safety Data Sheet
FLEXEPOXY 100 - PART B

MANUFACTURER:
ONTARIO
 111 Royal Group Cr.
 Vaughan, ON.
 L4H 1X9
 Tel: (416) 255-1111
 Fax: (416) 255-1729
 IN CASE OF EMERGENCY.

FLEXITILE LTD.
BRITISH COLUMBIA
 2829 Lake City Way
 Burnaby, BC
 V5A 2Z6
 Tel: (604) 420-4914
 FAX: (604) 420-0936
 CALL CANUTEC (613) 996-6666

Material Identification and Use

PRODUCT IDENTIFIER..... FLEXEPOXY 100 - PART B
 PRODUCT USE..... 100% SOLIDS EPOXY GROUTING & SETTING COMPOUND
 WHMIS CLASSIFICATION..... CLASS D, DIVISION 2B CLASS E

Hazardous Ingredients of Materials

CHEMICAL IDENTITY	CONCENTRATION	CAS#/NA#/UN#	LD(50)	LC(50)
TETRAETHYLENE			ORL-RAT 205MG/KG	
PENTAMINE	0.5-1.5%	112-57-2	DML-RBT 660MG/KG	N/AV
TALL OIL FATTY ACID	4.5-6.0%	68953-36-6	N/AV	N/AV
BENZYL ALCOHOL	15-30%	100-51-6	ORL-RAT 1230MG/KG	
			DRM-RBT 2000MG/KG	N/AV

All ingredients are listed within or exempted from US TSCA and Canadian DSL

Physical Data For Product

PHYSICAL STATE.....	LIQUID		
ODOUR AND APPEARANCE.....	AMMONIACAL, AMBER LIQUID		
ODOUR THRESHOLD.....	NOT AVAILABLE		
SPECIFIC GRAVITY.....	1.0 AT 77DEG F	VAPOUR PRESSURE.....	NOT AVAILABLE
VAPOUR DENSITY (air=1).....	NOT AVAILABLE	EVAPORATION RATE.....	NOT AVAILABLE
BOILING POINT.....	NOT AVAILABLE	FREEZING POINT.....	NOT AVAILABLE
pH.....	NOT AVAILABLE		
CALCULATED VOC CONTENT	< 20 GRMS/LITRE		

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY.....
 MEANS OF EXTINCTION..... DRY SAND, DRY CHEMICAL, "ALCOHOL" FOAM, CARBON DIOXIDE.
 FLASHPOINT AND METHOD OF DETERMINATION..... 195C (PENSKY MARTENS CLOSED CUP)
 UPPER EXPLOSION LIMIT (% BY VOL).. NOT AVAILABLE
 LOWER EXPLOSION LIMIT (% BY VOL).. NOT AVAILABLE
 AUTO-IGNITION TEMPERATURE..... NOT AVAILABLE
 FLAMMABILITY CLASSIFICATION..... NOT REGULATED
 HAZARDOUS COMBUSTION PRODUCTS..... TOXIC FUMES WILL EVOLVE WHEN THIS MATERIAL IS INVOLVED IN A FIRE.
 EXPLOSION DATA..... NOT AVAILABLE
 SENSITIVITY TO STATIC DISCHARGE... NOT AVAILABLE

Reactivity Data

CHEMICAL STABILITY..... STABLE UNDER NORMAL CONDITIONS.
 INCOMPATIBLE MATERIALS..... AVOID BRINGING INTO CONTACT WITH STRONG OXIDIZING i.e. PERCHLORATES, NITRATES ETC. OR MINERAL ACIDS i.e. SULPHURIC, PHOSPHORIC ACIDS ETC..
 CONDITIONS TO AVOID..... EXPOSURE TO EXCESSIVE HEAT.
 HAZARDOUS DECOMPOSITION PRODUCTS: IRRITATING TOXIC FUMES AT ELEVATED TEMPERATURES i.e. CARBON MONOXIDE, CARBON DIOXIDE & OXIDES OF NITROGEN.

Toxicological Properties of Product

ROUTES OF ENTRY

SKIN CONTACT.....	MAY CAUSE DRYNESS, DEFATTING, ITCHING AND/OR RASH.
SKIN ABSORPTION.....	MAY BE ABSORBED BY SKIN.
EYE.....	CAUSES TRANSIENT IRRITATION, REDNESS, AND DISCOMFORT.
INHALATION.....	IRRITATION OF RESPIRATORY TRACT.
INGESTION.....	MAY CAUSE DAMAGED TO MUCOUS MEMBRANE, NAUSEA UNLESS TREATED PROMPTLY.
ACUTE OVER EXPOSURE EFFECTS.....	REFER TO ROUTE OF ENTRY.
CHRONIC OVER EXPOSURE EFFECTS.....	PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSE.
EXPOSURE LIMITS.....	NOT AVAILABLE
IRRITANCY OF PRODUCT.....	EYE AND RESPIRATORY TRACT IRRITANT.
SENSITIZATION TO MATERIAL.....	MAY CAUSE SKIN SENSITIZATION.
CARCINOGENICITY, REPRODUCTIVE EFFECTS.....	NONE KNOWN
TERATOGENICITY, MUTAGENICITY.....	NONE KNOWN
TOXICOLOGICALLY SYNERGISTIC PRODUCTS.....	NONE KNOWN

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT.....

WEAR IMPERMEABLE GLOVES, PROTECTIVE CREAMS, SPLASH-PROOF GOGGLES OR SAFETY SPECTACLES WITH SIDE SHIELDS. NIOSH APPROVED RESPIRATORY PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL. FOR EMERGENCIES, A SELF-CONTAINED BREATHING APPARATUS OR A FULL-FACE RESPIRATOR IS RECOMMENDED.

VENTILATION..... BREATHING OF VAPOURS MUST BE AVOIDED.

VENTILATION MUST BE SUFFICIENT TO CONTROL VAPOURS. THIS MATERIAL SHOULD BE CONFINED AS FAR AS POSSIBLE WITHIN SEALED OR COVERED EQUIPMENT IN WHICH CASE, NORMAL VENTILATION SHOULD BE ADEQUATE. SPECIAL (LOCAL) VENTILATION WILL BE NEEDED IN AREAS WHERE VAPOURS ARE EXPECTED TO BE VENTED.

LEAK AND SPILL PROCEDURES: CONTAIN SPILL. ABSORB WITH SAND OR SAW DUST. PLACE IN CONTAINERS FOR DISPOSAL. FLUSH AREA WITH WATER SPRAY. AVOID CONTAMINATION OF GROUND AND SURFACE WATER. SHOULD CONTAMINATION OCCUR NOTIFY PROPER AUTHORITIES.

WASTE DISPOSAL..... DISPOSE IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL & FEDERAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT:

WEAR PROTECTIVE CLOTHING. OPEN ENCLOSED SPACES TO OUTSIDE ATMOSPHERE. AVOID CONTAMINATION OF GROUND OR SURFACE WATERS. POTENTIAL FOR CARBON MONOXIDE AND/OR NITROUS OXIDES GENERATION IN A FIRE MUST BE RECOGNIZED. MAINTAIN GOOD PERSONAL HYGIENE. WASH THOROUGHLY AFTER HANDLING. EXAMINE PROTECTIVE GLOVES BEFORE USING. DISCARD EVIDENCE OF CRACK OR HOLES. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID BREATHING VAPOURS OR MISTS. VENTILATE ADEQUATELY. OTHERWISE WEAR AN APPROPRIATE BREATHING APPARATUS. HANDLE AWAY FROM ALL SOURCES OF IGNITION. AVOID SMOKING.

STORAGE REQUIREMENTS: STORE AWAY FROM INCOMPATIBLE MATERIALS, OXIDISING MATERIALS. STORE AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE IN A COOL, WELL-VENTILATED AND DRY PLACE.

SPECIAL SHIPPING INFORMATION: NOT REGULATED

First Aid Measures

SPECIFIC FIRST AID PROCEDURES.....

EYE CONTACT: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES, WHILE HOLDING EYELID APART TO ENSURE COMPLETE IRRIGATION OF ALL EYE AND LID TISSUE. CONSULT PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING. VOMITING WILL CAUSE FURTHER DAMAGE TO THE THROAT. GET MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR. CONTACT PHYSICIAN. IF NECESSARY ADMINISTER OXYGEN.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH SOAP & WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN. WASH CONTAMINATED CLOTHING THOROUGHLY BEFORE RE-USE. DISCARD CONTAMINATED SHOES.

Preparation Date of Material Safety Data Sheet

PREPARED BY..... CHIEF CHEMIST
PHONE NUMBER OF PREPARER..... 416-255-1111 FAX: 416-255-1729
DATE PREPARED..... 15 March 2011

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

...FLEX TILE LTD.